

Sigen Hybrid Inverter

5.0 – 25.0 kW Three Phase



- Battery ready, future proof
- DC ground-fault protection
- DC/AC ratio up to 1.6
- Up to 4 MPP trackers
- IP66 protection rating

www.sigenenergy.com

Sigen Hybrid Inverter 5.0–25.0 kW Three Phase

Preliminary

Sigen Hybrid	5.0 TP	6.0 TP	8.0 TP	10.0 TP	12.0 TP	15.0 TP	17.0 TP	20.0 TP	25.0 TP	Units
DC Input										
Max. PV power	8000	9600	12800	16000	19200	24000	27200	32000	40000	W
Max. DC input voltage					1100					V
Nominal DC input voltage					600					V
Start-up voltage					180					V
MPPT voltage range					160 ~ 1000				V	
Number of MPP. trackers	2			3			4			
Number of PV strings per MPPT					1					
Max. input current per MPPT					16					A
Max. short-circuit current per MPPT					20					A
AC Output (on-grid)										
Nominal output power	5000	6000	8000	10000	12000	15000	17000	20000	25000	W
Max. output apparent power	5500	6600	8800	11000	13200	16500	18700	22000	27500	VA
Nominal output current	7.6	9.1	12.2	15.2	18.2	22.8	25.8	30.4	38.0	A
Max. output current	8.4	10.0	13.4	16.7	20.1	25.1	28.4	33.4	41.8	A
Nominal output voltage					380 / 400				V	
Nominal grid frequency					50 / 60				Hz	
Power factor					0.8 leading ~ 0.8 lagging					
Total current harmonic distortion					THDi < 2%					
Efficiency										
Max. efficiency					98.5%					
European efficiency					98.0%					
Additional Features										
Compatible battery module					SigenStor BAT 5.0 / 8.0					
Number of modules per controller					1 ~ 6				pcs	
Battery module voltage range					600 ~ 900				V	
Peak output power (10 seconds)	7500	9000	12000	15000	18000	22500	25500	30000	30000	W
Nominal output voltage					380 / 400				V	
General Data										
Dimensions (W / H / D)					700 / 300 / 283				mm	
Weight					30				kg	
Storage temperature range					-40 ~ 70				°C	
Operating temperature range					-30 ~ 60				°C	
Relative humidity range					0% ~ 95%					
Max. operating altitude					4000				m	
Cooling					Smart air cooling					
Ingress protection rating					IP66					
Noise emission					< 45				dB	
Installation method					Wall-mounted					

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.

