

Sigen Hybrid Inverter

5.0 – 25.0 kW Three Phase



- Battery ready, future proof
- DC ground-fault protection
- DC/AC ratio up to 1.6
- Up to 4 MPP trackers
- IP66 protection rating

Sigen Hybrid Inverter 5.0–25.0 kW Three Phase

Preliminary

Sigen Hybrid	5.0 TP	6.0 TP	8.0 TP	10.0 TP	12.0 TP	15.0 TP	17.0 TP	20.0 TP	25.0 TP	Units	
DC Input											
Max. PV power	8000	9600	12800	16000	19200	24000	27200	32000	40000	W	
Max. DC input voltage										1100	V
Nominal DC input voltage										600	V
Start-up voltage										180	V
MPPT voltage range										160 ~ 1000	V
Number of MPP trackers	2			3			4				
Number of PV strings per MPPT										1	
Max. input current per MPPT										16	A
Max. short-circuit current per MPPT										20	A
AC Output (on-grid)											
Nominal output power	5000	6000	8000	10000	12000	15000	17000	20000	25000	W	
Max. output apparent power	5500	6600	8800	11000	13200	16500	18700	22000	27500	VA	
Nominal output current	7.6	9.1	12.2	15.2	18.2	22.8	25.8	30.4	38.0	A	
Max. output current	8.4	10.0	13.4	16.7	20.1	25.1	28.4	33.4	41.8	A	
Nominal output voltage										380 / 400	V
Nominal grid frequency										50 / 60	Hz
Power factor										0.8 leading ~ 0.8 lagging	
Total current harmonic distortion										THDi < 2%	
Efficiency											
Max. efficiency										98.5%	
European efficiency										98.0%	
Additional Features											
Compatible battery module										SigenStor BAT 5.0 / 8.0	
Number of modules per controller										1 ~ 6	pcs
Battery module voltage range										600 ~ 900	V
Peak output power (10 seconds)	7500	9000	12000	15000	18000	22500	25500	30000	30000	W	
Nominal output voltage										380 / 400	V
General Data											
Dimensions (W / H / D)										700 / 300 / 283	mm
Weight										30	kg
Storage temperature range										-40 ~ 70	°C
Operating temperature range										-30 ~ 60	°C
Relative humidity range										0% ~ 95%	
Max. operating altitude										4000	m
Cooling										Smart air cooling	
Ingress protection rating										IP66	
Noise emission										< 45	dB
Installation method										Wall-mounted	

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigen Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.