



SIGENERGY



Sigen Hybrid Inverter

3.0–6.0 kW Single Phase

- Battery ready for future expansion
- Slimmest design, less intall. requirements
- Fan-less design, powerful yet quiet
- IP66 protection rating, worry-free usage

NEW

Sigen Hybrid Inverter 2.0–6.0 kW Single Phase

Preliminary

Sigen Hybrid	2.0 SP2	3.0 SP2	3.6 SP2	4.0 SP2	4.6 SP2	5.0 SP2	6.0 SP2	Units
DC Input (from PV)								
Max. PV power	4000	6000	7360	8000	9200	10000	12000	W
Max. DC input voltage				600				V
Nominal DC input voltage				350				V
Start-up voltage				100				V
MPPT voltage range				50 ~ 550				V
Number of MPP trackers				2				
Number of PV strings per MPPT				1				
Max. input current per MPPT				16				A
Max. short-circuit current per MPPT				22				A
Battery Connection								
Battery controller models				SigenStor BC				
Battery module models				SigenStor BAT series				
Number of modules per controller				1 ~ 6		pcs		
Battery module voltage range				300 ~ 600		V		
AC Output (on-grid)								
Nominal output power	2000	3000	3680	4000	4600	5000	6000	W
Max. output apparent power	2200	3300	3680	4400	5000	5500	6600	VA
Nominal output current	9.1	13.6	16.0	18.2	20.9	22.7	27.3	A
Max. output current	10.0	15.0	16.0	20.0	22.7	25.0	30.0	A
Nominal output voltage	220 / 230 / 240							V
Nominal grid frequency	50 / 60							Hz
Power factor	0.8 leading ~ 0.8 lagging							
Total current harmonic distortion	THDi < 3%							
AC Output (backup)								
Peak output power (10 seconds)	3000	4500	5520	6000	6900	7500	9000	W
Nominal output voltage	220 / 230 / 240							V
Nominal output frequency	50 / 60							Hz
Power factor	0.8 leading ~ 0.8 lagging							
Total voltage harmonic distortion	THDi < 3%							
Disruption time of backup switch ¹	0							ms
Efficiency								
Max. efficiency	98.6%							
European efficiency	97.5%	98.0%	98.1%	98.2%	98.3%	98.3%	98.3%	
Protection								
Safety protection feature	DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter, AC overcurrent/overvoltage/short-circuit protection, Type II DC/AC surge protection, Anti-islanding protection							
General Data								
Dimensions (W / H / D)	373 / 473 / 99							mm
Weight	11.5							kg
Storage temperature range	-40 ~ 70							°C
Operating temperature range	-30 ~ 60							°C
Relative humidity range	0% ~ 95%							
Max. operating altitude	4000							m
Cooling	Natural convection							
System ingress protection rating	IP66							
Communication	WLAN / Fast Ethernet / RS485 / Sigen CommMod (4G/3G/2G)							
Installation method	Wall-mounted							
Night consumption	2.5							W
Noise	25							dB

1. This document reflects current technology and is subject to change without notice. Refer to the Sigenenergy website for the latest information.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.