



Sigen Utility PV Inverter

Sigen PV 400H2 & 370H2

Sigen PV Inverter

Sigen PV	400H2	370H2	Units
DC Input			
Max. DC input voltage	1500		V
Start-up voltage	520		V
Nominal DC input voltage	1080		V
MPPT voltage range	480 ~ 1500		V
Number of MPP. trackers	14		
Number of PV strings per MPPT	2		
Max. input current per MPPT	40		A
Max. short-circuit current per MPPT	60		A
AC Output			
Nominal output active power	360,000	333,000	W
Max. output apparent power	396,000	366,300	VA
Max. output active power (cosφ=1)	396,000	366,300	W
Nominal output current	259.9	240.4	A
Max. output current	285.8	264.4	A
Nominal output voltage	800, 3W+PE		Vac
Nominal grid frequency	50 / 60		Hz
Power factor	0.8 leading ~ 0.8 lagging		
Total current harmonic distortion	THDi < 1%		
Efficiency			
Max. efficiency	99.0%		
European efficiency	98.8%		
Protection			
DC switch	Supported		
PV / Output terminal overtemperature protection	Supported		
Anti-islanding protection	Supported		
AC overcurrent protection	Supported		
DC reverse polarity protection	Supported		
DC surge protection	Type II (Default) / Type I (Optional)		
AC surge protection	Type II		
Insulation monitoring	Supported		
AFCI	Optional		
Residual current monitoring	Supported		
General Data			
Dimensions (W / H / D)	1080 / 860 / 409		mm
Weight ¹	140		kg
Nighttime power consumption	4.8		W
Operating temperature range	-30 ~ 60		°C
Relative humidity range	0% ~ 100%		
Max. operating altitude	5000 (Derating at 4000 m)		m
Cooling	Smart air cooling		
DC connection type	H4 Pro		
AC connection type	OT/DT terminal		
Ingress protection rating	IP66		
Anti-corrosion protection	C5-M (Default) / C5-H (Optional)		
Communication & Display			
FE (Fast Ethernet)	Supported		
PLC (AC)	Supported		
WLAN + APP	Supported		
LED indicators	Supported		

1. The actual weight may vary by ±10%. Please refer to the actual delivered product. The specification is for reference only.

Disclaimer: The information in this file is provided on "as is" basis. To the fullest extent permitted by law, Sigenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.