



SigenStack

Innovative modular energy storage system



- Pack-level safety protection, precise thermal runaway control
- Higher energy density saves space and eases site selection
- IP66-rated design eliminates regular and complex O&M
- Pack-level active balancing, no need for on-site SOC calibration
- Modular design, stackable installation & ultra-fast commissioning


C&I Energy Storage System

SigenStack BC	M2-0.5C ¹	M2-0.5C-BST	M2-1C-BST	Units
Max. output current (to inverter)		180		A
Max. input current (from inverter)		180		A
Operating voltage range		550 ~ 1,100		V
Nominal charge/discharge current of battery	157	157	314	A
Weight	50	60	60	kg
Dimensions (W / H / D)		770 / 248 / 363		mm
Communication		CAN		
Compatible inverter		Sigen C&I Hybrid Inverter Series		

	SigenStack BAT 12.0		Units
Performance Specification			
Battery type	LiFePO4		
Cell capacity	314		Ah
Cycle life ²	10,000		
Total energy capacity per module	12.06		kWh
Weight	105		kg
Dimensions (W / H / D)	770 / 300 / 363		mm
Nominal charge / discharge rate	0.5C		
Max. charge / discharge rate	1C		
System configuration quantity range	4 ~ 21		pcs
Max. system energy capacity	253		kWh

System General Data			
Max. number of modules per stack	7		pcs
Max. number of modules per system	21		pcs
Fire suppression system	Aerosol, smoke sensor and exhausting system		
Dimensions of base (W / H / D)	770 / 195 / 363		mm
Storage temperature range	-25 ~ 60		°C
Operating temperature range	-20 ~ 55		°C
Relative humidity range	0% ~ 100%		
Max. operating altitude	4,000 (Derating at 2,000m)		m
Cooling	Smart air cooling		
System ingress protection rating	IP66		
Installation method	Floor standing		
Noise ³	< 65		dB

Standard Compliance			
Standard ⁴	IEC/EN 60730-1, UN 38.3, IEC/EN 62619, IEC/EN 63056, IEC/EN 62040, UL9540A		



Number of battery modules	4	5	6	7	pcs
Total energy capacity	48.24	60.3	72.36	84.42	kWh
Total weight	500	605	710	815	kg
Total height (with base and SigenStack BC)	1,643	1,943	2,243	2,543	mm
Total width	770				mm
Total depth	363				mm

- SigenStack BC M2-0.5C can only be used in applications where an on-grid energy storage system with ≥ 20 battery modules operates under 380/400V grid voltage. For other scenarios, please utilize the battery controller with 'BST' model.
- This is provided by the battery cell manufacturer. Based on cell test condition of 25±2°C, 0.5C charge and discharge rate and SOH=60%.
- Noise level is tested based on the rated operating conditions (25 °C ambient temperature, 0.5CP charge/discharge rate, 400Vac output voltage).
- For all standards refer to the certificates category on the Sigenenergy website.
- This document reflects current technology and is subject to change without notice. Refer to the Sigenenergy website for the latest information.