

# Sigen Energy Gateway



- Multiple Sigen C&I inverters connections supported for micro-grid system
- Seamless switchover, ensuring 0ms load-side disruption
- Built-in bypass circuit for enhanced system reliability
- Supports diesel generator connection & smart control
- Real-time current monitoring with 350ms anti-backflow protection

| Sigen Gateway                                 | C600-B                            | C1200-B | C1600-B               | C2000-B | C2400-B | Units |
|-----------------------------------------------|-----------------------------------|---------|-----------------------|---------|---------|-------|
| Grid Connection                               |                                   |         |                       |         |         |       |
| Grid connection type                          | Three phase                       |         |                       |         |         |       |
| Nominal AC voltage                            | 380 ~ 400                         |         |                       |         |         | V     |
| Nominal AC current                            | 912                               | 1,824   | 2,432                 | 3,039   | 3,647   | A     |
| Nominal AC power                              | 600                               | 1,200   | 1,600                 | 2,000   | 2,400   | kW    |
| Nominal AC frequency                          | 50 / 60                           |         |                       |         |         | Hz    |
| Disruption time of backup switch <sup>1</sup> | 0                                 |         |                       |         |         | ms    |
| AC Output to Backup Port                      |                                   |         |                       |         |         |       |
| Nominal AC voltage                            | 380 ~ 400                         |         |                       |         |         | V     |
| Nominal AC current                            | 912                               | 1,824   | 2,432                 | 3,039   | 3,647   | A     |
| Nominal AC power                              | 600                               | 1,200   | 1,600                 | 2,000   | 2,400   | kW    |
| Nominal AC frequency                          | 50 / 60                           |         |                       |         |         | Hz    |
| Overvoltage category                          | III                               |         |                       |         |         |       |
| Inverter Connection                           |                                   |         |                       |         |         |       |
| Number of connection ports                    | 10                                | 20      | 30                    | 30      | 30      |       |
| Nominal AC voltage                            | 380 ~ 400                         |         |                       |         |         | V     |
| Max. AC input current                         | 190                               | 190     | 190                   | 190     | 190     | A     |
| Nominal AC power                              | 125                               | 125     | 125                   | 125     | 125     | kW    |
| Smart Port Connection                         |                                   |         |                       |         |         |       |
| Generator output voltage                      | 380 ~ 400                         |         |                       |         |         | V     |
| Nominal AC current                            | 912                               | 1,824   | 2,432                 | 3,039   | 3,647   | A     |
| Nominal AC power                              | 600                               | 1,200   | 1,600                 | 2,000   | 2,400   | kW    |
| Generator 2-wire start                        | Supported                         |         |                       |         |         |       |
| General Data                                  |                                   |         |                       |         |         |       |
| Dimensions (W / H / D)                        | 1,800 / 2,300 / 1,270             |         | 4,000 / 2,200 / 1,000 |         |         | mm    |
| Weight                                        | 1,100                             | 1,300   | 2,200                 | 2,500   | 2,800   | kg    |
| Storage temperature range                     | -40 ~ 70                          |         |                       |         |         | °C    |
| Operating temperature range <sup>2</sup>      | -30 ~ 55                          |         |                       |         |         | °C    |
| Relative humidity range                       | 0% ~ 95%                          |         |                       |         |         |       |
| Max. operation altitude <sup>2</sup>          | 4,000                             |         |                       |         |         | m     |
| Cooling                                       | Smart air cooling                 |         |                       |         |         |       |
| Ingress protection rating                     | IP20                              |         |                       |         |         |       |
| Communication                                 | Fast Ethernet, RS485, dry contact |         |                       |         |         |       |
| Installation method                           | Ground-mounted                    |         |                       |         |         |       |

1. This refers to the load-side disruption time, to achieve this functionality Sigen Energy Gateway needs to be used together with Sigen Hybrid Inverter and Sigen Battery. Test conditions: In the open-circuit state of the power grid, the nominal power of the Sigen Hybrid Inverter is higher than the total power of the backup loads.
2. Please consult Sigenergy for detailed power derating information and customized requirements.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.