



Sigen Power Sensor

- 1% high-accuracy power detection for precise control
- LCD real-time info display, easy to operate and check
- Integrates smoothly with Sigenenergy devices, no need for setup
- Top class 100 A direct connection in single phase grid system
- Support export/import limitations and ready for AI evolving
- 100 ms data refresh rate, instantaneous data feed

Sigen Power Sensor

Sigen Sensor	SP-DH	SP-CT-DH	TP-DH	TP-CT-DH	Units
Power Supply					
Grid connection type	1P2W		3P4W		
AC input voltage range	184 ~ 276		320 ~ 480		V
Nominal AC frequency			50 / 60		Hz
Max. operating current			100		A
Measurement Accuracy					
Voltage accuracy			0.5%		
Current accuracy			0.5%		
Power accuracy			1%		
Frequency accuracy			0.2%		
Communication					
Interface			RS485		
Baud rate			9600		bps
Protocol			Modbus RTU		
General Data					
Dimensions (W / H / D)	36 / 100 / 63	18 / 118 / 64	72 / 100 / 66	72 / 94.5 / 65	mm
Weight	0.23	0.10	0.40	0.28	kg
Storage temperature range			-40 ~ 70		°C
Operating temperature range			-30 ~ 60		°C
Relative humidity range			0% ~ 90%		
Ingress protection rating			IP51		
Installation method			DIN Rail 35 mm		
CT Accessory					
Number of CT	-	1	-	3	
Cable length of CT	-	1	-	1	m
Inner diameter of CT	-	16	-	16	mm
Weight of CT	-	0.11	-	0.11	kg
Max. operating current of CT	-	120	-	120	A
Output current of CT	-	40	-	40	mA

Disclaimer: The information in this file is provided on an “as is” basis. To the fullest extent permitted by law, Sigenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.