





Sigen Battery

- Large cell capacity, low voltage & durable
- Multi-layer full battery safety protection
- Visible battery status on mySigen APP
- Quick connectors for fast installation
- AI enablement, optimized battery cycle life
- Parallel connections for flexible battery mix

Sigen Battery 5.0 / 8.0 kWh

SigenStor BAT	5.0		8.0	Units
Performance Specification				
Battery type	LiFePO ₄			
Total energy capacity	5.38		8.06	kWh
Usable energy capacity*	5.2		7.8	kWh
Battery modules voltage range (single phase system)	300 ~ 600			V
Battery modules voltage range (three phase system)	600 ~ 900			V
Max. charge / discharge power	2500		4000	W
Peak charge / discharge power (10 seconds)	3750		6000	W
General Data				
Weight	57		73	kg
Dimensions (W / H / D)	767 / 270 / 260			mm
Storage temperature range	-25 ~ 60			°C
Operating temperature range	-20 ~ 55			°C
Relative humidity range	5% ~ 95%			
Max. operating altitude	4000			m
Cooling	Natural convection			
Ingress protection rating	IP66			
Noise emission	< 30			dB
Installation method	Floor standing / Wall-mounted			

* Test conditions: 100% depth of discharge, 0.2C rate charge & discharge averagely at 25°C.



Number of battery modules	1	2	3	4	5	6	pcs
Total energy capacity	8.06	16.12	24.18	32.24	40.3	48.36	kWh
Max. charge / discharge power	4	8	12	16	20	24	kW
Peak charge / discharge power (10 seconds)	6	12	18	24	30	36	kW
Total weight	91	164	237	310	383	456	kg
Total height (with base)	640	910	1180	1450	1720	1990	mm
Total width (with decorative covers)	850						mm
Total depth (with decorative covers)	260						mm

The combination of SigenStor BAT 8.0 + SigenStor EC single phase as example

Disclaimer: The information in this file is provided on an “as is” basis. To the fullest extent permitted by law, Sigenenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.