



# Sigen Hybrid Inverter

3.0 – 6.0 kW Single Phase



- Battery ready, future proof
- DC ground-fault protection
- DC/AC ratio up to 2
- Dual MPP trackers
- IP66 protection rating

## Sigen Hybrid Inverter 3.0–6.0 kW Single Phase

Sigen Hybrid	3.0 SP	3.6 SP	4.0 SP	4.6 SP	5.0 SP	6.0 SP	Units	
<b>DC Input</b>								
Max. PV power	6000	7360	8000	9200	10000	12000	W	
Max. DC input voltage							600	V
Nominal DC input voltage							350	V
Start-up voltage							100	V
MPPT voltage range							50 ~ 550	V
Number of MPP trackers							2	
Number of PV strings per MPPT							1	
Max. input current per MPPT							16	A
Max. short-circuit current per MPPT							20	A
<b>AC Output (on-grid)</b>								
Nominal output power	3000	3680	4000	4600	5000	6000	W	
Max. output apparent power	3300	3680	4400	5000	5500	6600	VA	
Nominal output current	13.6	16.0	18.2	20.9	22.7	27.3	A	
Max. output current	15.0	16.0	20.0	22.7	25.0	30.0	A	
Nominal output voltage							220 / 230 / 240	V
Nominal grid frequency							50 / 60	Hz
Power factor							0.8 leading ~ 0.8 lagging	
Total current harmonic distortion							THDi < 2%	
<b>Efficiency</b>								
Max. efficiency							98.0%	
European efficiency	97.0%	97.1%	97.2%	97.3%	97.4%	97.4%		
<b>Additional Features</b>								
Compatible battery module							SigenStor BAT 5.0 / 8.0	
Number of modules per controller							1 ~ 6	pcs
Battery module voltage range							300 ~ 600	V
Peak output power (10 seconds)	4500	5520	6000	6900	7500	9000	W	
Nominal output voltage							220 / 230 / 240	V
<b>General Data</b>								
Dimensions (W / H / D)							700 / 300 / 268	mm
Weight							18	kg
Storage temperature range							-40 ~ 70	°C
Operating temperature range							-30 ~ 60	°C
Relative humidity range							0% ~ 95%	
Max. operating altitude							4000	m
Cooling							Natural convection	
Ingress protection rating							IP66	
Noise emission							< 30	dB
Installation method							Wall-mounted	