Sigen Hybrid Inverter

5.0 - 25.0 kW Three Phase



- Battery ready, future proof
- DC ground-fault protection
- DC/AC ratio up to 1.6
- Up to 4 MPP trackers
- IP66 protection rating

www.sigenergy.com

Sigen Hybrid Inverter 5.0-25.0 kW Three Phase

Preliminary

Sigen Hybrid	5.0 TP	6.0 TP	8.0 TP	10.0 TP	12.0 TP	15.0 TP	17.0 TP	20.0 TP	25.0 TP	Units
DC Input										
Max. PV power	8000	9600	12800	16000	19200	24000	27200	32000	40000	W
Max. DC input voltage	1100									V
Nominal DC input voltage	600									V
Start-up voltage	180									V
MPPT voltage range	160 ~ 1000									V
Number of MPP. trackers	2			3			4			
Number of PV strings per MPPT	1									
Max. input current per MPPT	16									A
Max. short-circuit current per MPPT	20									A
AC Output (on-grid)										
Nominal output power	5000	6000	8000	10000	12000	15000	17000	20000	25000	W
Max. output apparent power	5500	6600	8800	11000	13200	16500	18700	22000	27500	VA
Nominal output current	7.6	9.1	12.2	15.2	18.2	22.8	25.8	30.4	38.0	A
Max. output current	8.4	10.0	13.4	16.7	20.1	25.1	28.4	33.4	41.8	A
Nominal output voltage	380 / 400									V
Nominal grid frequency	50 / 60									Hz
Power factor	0.8 leading ~ 0.8 lagging									
Total current harmonic distortion	THDi < 2%									
Efficiency										
Max. efficiency	98.5%									
European efficiency	98.0%									
Additional Features										
Compatible battery module	SigenStor BAT 5.0 / 8.0									
Number of modules per controller	1 ~ 6									pcs
Battery module voltage range	600 ~ 900									V
Peak output power (10 seconds)	7500	9000	12000	15000	18000	22500	25500	30000	30000	W
Nominal output voltage	380 / 400									V
General Data										
Dimensions (W / H / D)	700 / 300 / 283									mm
Weight	30									kg
Storage temperature range	-40 ~ 70									°C
Operating temperature range	-30 ~ 60									°C
Relative humidity range	0% ~ 95%									
Max. operating altitude	4000									m
Cooling	Smart air cooling									
Ingress protection rating	IP66									
Noise emission	< 45									dB
Installation method	Wall-mounted									

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.

PLUG&PLAY ENERGY