



solis

20<sup>th</sup>  
ANNIVERSARY



## Grid-Tied Inverters

### S6-GC(100-125)K

8/10 MPPT | 42A/36A per MPPT



#### Safety, Intelligent Prevention

- Integrated meteorological equipment, intelligent system inefficiency warning
- AI-based millisecond arc protection (AFCI)
- Real time PV grounding detection and protection
- Arc fault and RSD (Rapid Shutdown) co-operation for improved fire safety (optional)



#### Innovation, Never Stops

- Master-slave export power control solution, flexible and fast control, support 10 units in parallel
- Dual independent RS485 ports, perfect adaptation to third-party integration
- Supports single and multiple genset applications without the need for an external genset controller
- The industry's first master-slave export power control+ three-phase unbalanced output control, allocate each phase power on demand, and flexibly compatible with various power grids (optional)

GINLONG TECHNOLOGIES CO., LTD.

t: +86 574 6580 2188 e: sales@ginlong.com  
w: solisinverters.com service@ginlong.com



## DATASHEET

## S6-GC(100-125)K

Models	100K	110K	125K	125K-HV
<b>Input DC</b>				
Max. input voltage	1100 V			
Rated voltage	600 V		720 V	
Start-up voltage	180 V			
MPPT voltage range	160 - 1000 V			
Max. input current	5 × (42 A / 36 A)			
Max. short circuit current	10 × 50 A			
MPPT number / Max. input strings number	10 / 20			
<b>Output AC</b>				
Rated output power	100 kW	110 kW	125 kW (@50°C 415Vac)	125kW
Max. apparent output power	110 kVA	121 kVA	125 kVA (@50°C 415Vac)	137.5 kVA
Max. output power	110 kW	121 kW	125 kW (@50°C 415Vac)	137.5 kW
Rated grid voltage	3/N/PE, 230 V / 400 V		3/N/PE, 230 V / 400 V, 240 V / 415 V	3/PE, 480 V
Rated grid frequency	50 Hz			
Rated grid output current	144.3 A	158.8 A	180.4 A	150.4 A
Max. output current	158.8 A	174.6 A	180.4 A	165.4 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)			
THDi	< 3%			
DC injection current	0.5%In			
<b>Efficiency</b>				
Max. efficiency	98.7%			
EU efficiency	98.3%			
<b>Protection</b>				
DC reverse-polarity protection	Yes			
Short circuit protection	Yes			
Output over current protection	Yes			
Insulation resistance monitoring	Yes			
Residual current detection	Yes			
Surge protection	DC Type II / AC Type II			
Grid monitoring	Yes			
Anti-islanding protection	Yes			
Temperature protection	Yes			
Strings monitoring	Yes			
Night SVG function	Yes			
I/V Curve scanning	Yes			
Integrated AFCI 2.0	Optional			
Integrated PID recovery	Optional			
Integrated DC switch	Yes			
Integrated AC switch	Optional			
<b>General Data</b>				
Dimensions (W × H × D)	1014 × 567 × 345 mm			
Weight	96 kg			
Topology	Transformerless			
Self-consumption (night)	< 2 W			
Operating ambient temperature range	- 30 ~ +60°C			
Relative humidity	0 - 100%			
Ingress protection	IP66			
Cooling concept	Intelligent fan-cooling			
Max. operation altitude	4000 m			
Grid connection standard	G99, IEC61727, EN50549-1/2, VDE4110			
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4			
<b>Features</b>				
DC connection	MC4 connector			
AC connection	OT terminal (max. 240 mm <sup>2</sup> )			
Display	LCD			
Communication	RS485, Optional: S3-WIFI-ST, S3-GRPS-ST, PLC			