

M-Backup



We reserve the right to modify product specifications without notice. While efforts are made to ensure accuracy, this material does not constitute any direct or implied commitment, warranty, or guarantee by ATMOCE. All information is provided "as-is" and we disclaim liability for any reliance placed thereon.

Items	Unit	M-Backup	
What's in the box			
Combiner/Load breaker		1 × unit, 80 A, 2-pole	1 × unit, 80 A, 4-pole
Grid breaker		1 × unit, 80 A, 2-pole	1 × unit, 80 A, 4-pole
Bypass breaker		1 × unit, 80 A, 2-pole	1 × unit, 80 A, 4-pole
Electrical parameters			
Grid setup		Single-phase	Three-phase
Nominal voltage	V	220/230/240 Va.c.	220/380 Va.c., 230/400 Va.c., 3/N~
Operating voltage range (L to N)	V	184 to 276	
Nominal frequency	Hz	50/60	
Extended frequency range	Hz	45 to 65	
Max. combiner/load current	A	80	
Max. grid current	A	80	
Max. distribution panel current	A	80	
Overvoltage category		III	
Noise	dB	<25	
Altitude	m	3000	
Protection class		II	
Pollution degree		III	
Mechanical parameters			
Dimensions (W x H x D)	mm	447 × 389 × 124	
Weight	kg	3.6	6
Ambient temperature range	°C	-30 to 50	
Cooling		Natural convection	
Enclosure environmental rating		Outdoor, IP65	
Wire sizes ^a	mm ²	Combiner/Load side: 16 to 25 Grid side: 16 to 25 Distribution panel side:16 to 25	
Communication cable sizes		0.25 to 0.75	
Communication		CAN, DO	
Compliance			
Safety		IEC 61439-1/-2	
Health		IEC 62311	
EMC		EN 301 489-1/-17, IEC 61000-6-1/-2/-3/-4	
Radio spectrum		EN 300 328	

a. Refer to the local electrical regulations to select the cable size.