


C&I Energy Storage System

Preliminary

	SigenStack BC MI Series	Unit
Battery Controller		
Max. output current	180	A
Max. input current of inverter	180	A
Operating voltage range	550 ~ 1100	V
Dimensions (W / H / D)	770 / 235 / 363	mm
Weight	60	kg
Communication	CAN	
Compatible inverter	Sigen Hybrid Inverter Series	

	SigenStack BAT 11.0	Unit
Performance Specification		
Battery type	LiFePO4	
Total energy capacity per module	10.75	kWh
Weight	100	kg
Dimensions (W / H / D)	770 / 300 / 363	mm
Nominal charge / discharge rate	0.5C	
Max. charge / discharge rate	1C	
System configuration quantity range	4 ~ 21	PCS
Max. system energy capacity	225.8	kWh

General Data		
Fire suppression system	Aerosol, smoke sensor and exhausting system	
Max. operating altitude	4,000 (Derating at 2,000m)	m
Cooling	Smart air cooling	°C
System ingress protection rating	IP66	°C
Noise	70	dB
Operating temperature range	-20 ~ 55	°C
Relative humidity range	0% ~ 95% (non-condensing)	
Max. number of modules per stack	7	PCS
Max. number of modules per system	21	PCS
Dimensions of base (W / H / D)	770 / 195 / 363	mm
Installation method	Floor standing	



Number of battery modules	4	5	6	7	pcs
Total energy capacity	48.24	60.3	72.36	84.42	kWh
Total weight	480	580	680	780	kg
Total height (with base and SigenStack BC)	1,630	1,930	2,230	2,530	mm
Total width	770				mm
Total depth	363				mm

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.